

# Implementation of software organization at CERN (+ an update...)

Elisabetta Pennacchio, IPNL

- A stable and complete working environment for WA105 is available at CCIN2P3 from February 2015
- All software packages are also available: CRY, GENIE, Globes, NuFitter, Qscan (old and new version....)

```
2015 CRY
2015 GENIE
2015 GlobesSimu
2015 Qscan_version-1.0
2015 Qscan_v1.1
2015 WA105Soft_v1.0
2015 GENIE_inputfileforQscan -> /sps/hep/lbno/dataset/GENIE_inputfile_forQscan
2015 Qscan -> Qscan_v1.1
2015 Light_Simulation
2015 README
15:27 WA105Soft
15:31 WA105Soft_v3.0
```

- In order to be able to run at CERN the reconstruction during the 3x1x1 data taking the same working environment has also implemented on lxplus. It is an exact replication of what we have at the CCIN2P3.
- Next slides describe how to use Qscan at CERN and how to connect to the svn server

# Main directory: /afs/cern.ch/exp/wa105/Public

```
epennacc wa105-comp 2048 Jul 19 11:44 kits
epennacc wa105-comp 2048 Jul 19 11:58 dataset
epennacc wa105-comp 2045 Jul 19 15:11 WA105_setup.sh
epennacc wa105-comp 2048 Jul 20 19:14 WA105Soft
```

#### 3 sub-directories:

kits: external libraries and needed packages (ROOT, Geant,..., same versions installed at CCIN2P3 in \$KITS\_DIR)


dataset: files to be used an input to Qscan (field maps, light maps.... subsample of files available in /sps/hep/lbno/DATASET)

WA105Soft: simulation and reconstruction code

# Working environment

- The working environment is set by /afs/cern.ch/exp/wa105/Public/WA105Soft\_setup.sh This file defines the complete working environment for the CERN default bash shell (\$ROOTSYS, \$G4INSTALL, \$G3SYS,...) and also alias and variable to access eos and CASTOR
- André has prepared WA105Soft\_setup.csh for those who use csh
  - To source this file two possibilities are available:
    - 1) source the file manually at each login
    - 2) modify .bash\_profile to source WA105Soft\_setup.sh automatically at each login (should be preferred) →

## from home directory: Is -a



# **Validation**

To check that the environment is correctly set up and that simulation and reconstruction can be run, 10 events (muons in gun mode) have been generated and processed in the 3x1x1 and 6x6x6 configuration. Benchmark distributions have also been produced for raw data, hit and track reconstructions.

#### Output ROOT files are available:

```
[epennacc@lxplus0004 benchmark] pwd

/afs/cern.ch/exp/wa105/Public/WA105Soft/benchmark

[epennacc@lxplus0004 benchmark] ls -rtl *.root

-rw-r--r-. 1 epennacc wa105-comp 13281 Jul 21 14:13

-rw-r--r-. 1 epennacc wa105-comp 31860 Jul 21 14:13

-rw-r--r-. 1 epennacc wa105-comp 69384 Jul 21 14:13

-rw-r--r-. 1 epennacc wa105-comp 24485 Jul 21 14:14

-rw-r--r-. 1 epennacc wa105-comp 14621 Jul 21 14:14

bench recotask WA105 output 666 pass12.root

bench recotask WA105 output 666 pass12.root

bench recotask WA105 output 311 pass12.root

bench recotask WA105 output 311 pass12.root

bench recotask WA105 output 311 pass11.root
```

The same events have also been produced at CCIN2P3, and benchmark distributions are identical.

# To get the code

- Copy /afs/cern.ch/exp/wa105/Public/WA105Soft/WA105Soft.tgz in your working directory, unpack it and start working
- 2) Checkout the code from the svn server
  - → Instructions to ask for an account can be found here: <a href="http://lbnodemo.ethz.ch:8080/Plone/software/workbook/repositories/svn\_WA105.pdf/view">http://lbnodemo.ethz.ch:8080/Plone/software/workbook/repositories/svn\_WA105.pdf/view</a>)
  - → if you already have an account: copy the following files from your .ssh directory (from the machine you are using to connect to the svn)

```
key_for_svn.in2p3.fr
key_for_svn.in2p3.fr.pub
config
```

to the .ssh directory on lxplus

#### How to check out code:

```
[epennacc@lxplus094 WA105] style="font-size: style="font-size: left;" s
```

### How to commit:

```
[epennacc@lxplus094 Qscan] $ svn commit

Enter passphrase for key '/afs/cern.ch/user/e/epennacc/.ssh/key_for_svn.in2p3.fr':

Sending Qscan/WA105_example.datacard

Transmitting file data .

Committed revision 341.
```


# CONCLUSIONS

- A working environment to run Qscan has been set-up at CERN in view of the 3x1x1 data taking. It is a replication of the CCIN2P3 environment.
- The svn server already in use can be accessed from the CERN machines
- The same events have been generated and reconstructed at CERN and at CCIN2P3, and results are identical. No major problems showed up, but please note that this platform has been so far only tested by few people.
- One last point has to be stressed: CERN is phasing out AFS.
   This installation cannot be \*THE FINAL\* installation that will be used during WA105 life: for sure in the next months we will have to migrate it.

# Update on the code for purity measurement (code availability)

The method used to measure purity has been presented at the SB meeting of July 6<sup>th</sup> <a href="https://indico.fnal.gov/conferenceDisplay.py?confld=12481">https://indico.fnal.gov/conferenceDisplay.py?confld=12481</a>

#### The code is now available on svn




```
[pennacc@cca008 purity] $ more README
   How to run the code for purity measurement
You can find the following directories:
                                                                        readme
inc
src
work
the Makefile (and this README).
1) run make to get purity.exe (if needed)
> make
enter in work directory
  ed work
                                                                   Explanation of different files/directories
  ls -rtl
  purity.sh --> script to be used
  purity.exe -> ../purity.exe --> link to executable
   input --> directory for scripts and macros needed by purity.sh , you do not need to modify it
3) now you need to link a root file of recostructed data, reco.root
4) to run the code:
                                                  How to run the code
   source purity.sh reco.root
   this create a directory: purity reco ddmmyy hhmmss
   in purity reco ddmmyy hhmmss there are two relevant files:
   --> fitresult ddmmyy hhmmss.listing: ascii file with purity values for view 0 and view1 obtained from fit
   --> purity ddmmyy hhmmss.listing:: general information about input file (reco.root)
   A pdf file, purity ddmmyy hhmmss.pdf is also available
                                                                          List of output files
                                                                                                         10
Please note that the scripts ends in a root session
```

## An example:

```
[pennacc@cca008 purity] $ 1s -rt1
total 224
-rw-r--r-- 1 pennacc lbno 1113 Jul 20 08:51 README
drwxr-sr-x 2 pennacc lbno 512 Jul 20 08:51 inc
-rw-r--r-- 1 pennacc lbno 380 Jul 20 08:51 Makefile
drwxr-sr-x 2 pennacc 1bno 512 Jul 20 08:53 src
-rwxr-xr-x 1 pennacc lbno 211265 Jul 20 08:53 purity.exe
drwxr-sr-x 7 pennacc 1bno
                         8192 Jul 22 15:59 work
[pennacc@cca008 purity] cd work
[pennacc@cca008 work]$ date
                                                                           Enter in work directory
Fri Jul 22 16:00:19 CEST 2016
[pennacc@cca008 work] $ source purity.sh reco WA105 diagonale lt.root 🔶 —
                                                                           and run the code
---->processing input file
---->file reco WA105 diagonale lt.root will be analized
```

```
[pennacc@cca008 work] $ source purity.sh reco WA105 diagonale lt.root
---->processing input file
---->file reco WA105 diagonale lt.root will be analized
                                                                drift distance is divided in bins
---->fitting all histograms
---->creating directory and script
          WELCOME to ROOT
     Version 5.34/23 7 November 2014
    You are welcome to visit our Web site
            http://root.cern.ch
ROOT 5.34/23 (v5-34-23@v5-34-23, Jun 05 2015, 15:10:19 on linuxx8664qcc)
CINT/ROOT C/C++ Interpreter version 5.18.00, July 2, 2010
Type ? for help. Commands must be C++ statements.
Enclose multiple statements between { }.
root [0]
Processing fitbin.C...
Info in <TCanvas:: MakeDefCanvas>: created default TCanvas with name c1
root [0]
Processing fit mop.C...
 FCN=40.2725 FROM MIGRAD
                                              138 CALLS
                                                               139 TOTAL
                          STATUS=CONVERGED
                    EDM=1.04993e-09
                                     STRATEGY= 1
                                                      ERROR MATRIX ACCURATE
  EXT PARAMETER
                                               STEP
                                                           FIRST
 NO.
     NAME
                VALUE
                                 ERROR
                                               SIZE
                                                        DERIVATIVE
  1 p0
                 9.94469e-01 1.87160e-03 2.58584e-06 -7.30028e-03
                 3.07342e+03 8.22566e+00 1.13639e-02 -7.01392e-06
   2 p1
 FCN=46.8564 FROM MIGRAD
                          STATUS=CONVERGED
                                          137 CALLS
                                                               138 TOTAL
                                     STRATEGY= 1 ERROR MATRIX ACCURATE
                    EDM=1.45369e-06
  EXT PARAMETER
                                               STEP
                                                           FIRST
      NAME
                               ERROR
                                               SIZE DERIVATIVE
 NO.
                VALUE
                                                                                Purity is computed
   1 p0
                 9.89968e-01 1.79760e-03 2.74212e-06 3.18883e-01
                                                                               for the 2 views 12
                 3.07585e+03 8.05299e+00
                                          1.22804e-02 -1.45771e-04
 nfo in <TCanvas::Print>: pdf file purity.pdf has been created
```



## A directory has been created in purity/work

```
[pennacc@cca008 work] $ 1s -rt1

Jul 22 16:04 purity_reco_WA105_diagonale_lt_220716_160038

Name of input file run time:
format ddmmyy_hhmmss
```

# Contents of the directory:

```
[pennacc@cca008 purity reco WA105 diagonale lt 220716 160038] $ ls -rtl
total 144
-rw-r--r- 1 pennacc lbno 1971 Jul 22 16:00 purity reco WA105 diagonale lt.listing
-rw-r--r- 1 pennacc 1bno 54562 Jul 22 16:00 purity reco WA105 diagonale 1t.root
lrwxrwxrwx 1 pennacc lbno 31 Jul 22 16:00 fit.listing -> fitresult 220716 160038.listing
-rw-r--r-- 1 pennacc lbno 4357 Jul 22 16:00 fitbin.C
                                                                                                Output from
-rw-r--r 1 pennacc lbno 306 Jul 22 16:00 write macro.sh
                                                                                                 intermediate
-rw-r--r-- 1 pennacc lbno 1550 Jul 22 16:00 fit2 mop.input
lrwxrwxrwx 1 pennacc lbno 35 Jul 22 16:00 tbin.root -> purity reco WA105 diagonale lt.root
                                                                                                 steps and
-rw-r--r-- 1 pennacc lbno 7112 Jul 22 16:00 tbin mean.list
                                                                                                 service files
-rw-r--r-- 1 pennacc lbno 6794 Jul 22 16:00 tbin fit.list
-rw-r--r-- 1 pennacc lbno 6060 Jul 22 16:00 mop.input
-rw-r--r-- 1 pennacc lbno 446 Jul 22 16:00 fit1 mop.input
-rw-r--r-- 1 pennacc lbno 8056 Jul 22 16:00 fit mon.C
-rw-r--r-- 1 pennacc lbno 66 Jul 22 16:00 fitresult 220716 160038.listing
-rw-r--r-- 1 pennacc lbno 17382 Jul 22 16:00 purity 220716 160038.pdf
[pennacc@cca008 purity_reco_WA105_diagonale lt 220716 160038) more fitresult 220716 160038.listing
220716 160038
view 0: 3073.42 8.22566
view 1: 3075.85 8.05299
```